

. CTY 1035

		() °	rpm/min	Kg.					0		
					I	II			u	?	
8		160	90°	1000	5	*	*	*	*	*	*
		195	60°	1000	5	*	*	*	*	*	*
		155	60°	1000	5	*	*	*	*	*	*
		160	40°	1000	5	*	*	*	*	*	*
		110	30°	1000	5	*	*	*	*	*	*
		105		1000	5	*	*	*	*	*	*
1 x 15		100	60°	800	2	*	*	*	*	*	*
		95	60°	800	2	*	*	*	*	*	*
		90	50°	800	2	*	*	*	*	*	*
		85	40°	800	2	*	*	*	*	*	*
		75	30°	800	2	*	*	*	*	*	*
		70		800	2	*	*	*	*	*	*
0		60	40°	600	1,5	*	*	*	*	*	*
	#	55	30°	800	1	*	*	*	*	*	*
	#	50		800	1	*	*	*	*	*	*
		50	30°	800	2	*	*	*	*	*	*
.		25		800				*	*	*	*
	@	9		1000							
		4									
	1 & (M&W)	195	40°	800	5	*	*	*	*	*	*
	32	32	50°	800	2	*	*	*	*	*	*

60456

TexH

. CTY 1035

								EN60456	EN60456
230 /50 4.	175 W.	340 W.	30 W.	1950 W.	2200 W.	10 A.	0,05-0,8	45 L.	0,85 Kw.

- 1. -
- 2. -
-
-
-

- 3. -
- 4. -

(A)

(C1, C2, C3)

(H).

1

ACTIVA SYSTEM,

60%,

02

aquaplus 4^4

SENSOR ACTIVA SYSTEM,

03

« »

Mix&Wash.;

Mix&Wash,

5. -
B

(B)

6. -

(H).

(V),

(H)

OFF,

o

(

).

(V).

(G).

(

).

OFF.

(H),

(H)

(

2

),

(H),

(V G).

S

/

),

OFF