

● CASE SIZE & MAX RIPPLE CURRENT

Case size : D x L (mm)
Max ripple current : mA(rms) 105°C 120Hz

μF	V(Code)		6.3 (0J)		10 (1A)		16 (1C)	
	Code	Item	DxL	R.C.	DxL	R.C.	DxL	R.C.
47		470				→	5x11	90
100		101	5x11	110	5x11	120	5x11	130
220		221	5x11	160	5x11	180	6.3x11	220
330		331	6.3x11	220	6.3x11	250	8x11.5	310
470		471	6.3x11	270	6.3x11	290	8x11.5	370
1000		102	8x11.5	460	10x12.5	530	10x16	630
2200		222	10x16	760	10x20	910	12.5x20	1050
3300		332	10x20	990	12.5x20	1140	12.5x25	1340
4700		472	12.5x20	1200	12.5x25	1420	16x25	1510
6800		682	12.5x25	1500	16x25	1600	16x31.5	1860
10000		103	16x25	1660	16x35.5	2040	18x35.5	2270
15000		153	16x35.5	2140	18x35.5	2370	20x40	2550
22000		223	18x40	2590	20x40	2830	22x50	3380
33000		333	22x50	3390	22x50	3470	25x50	3790

All blank voltage on sleeve marking is the same voltage as" → "point to.

μF	V(Code)		25 (1E)		35 (1V)		50 (1H)	
	Code	Item	DxL	R.C.	DxL	R.C.	DxL	R.C.
0.1		0R1				→	5x11	5
0.22		R22				→	5x11	8
0.33		R33				→	5x11	10
0.47		R47				→	5x11	12
1		010				→	5x11	17
2.2		2R2				→	5x11	25
3.3		3R3				→	5x11	31
4.7		4R7				→	5x11	36
10		100	5x11	43	5x11	49	5x11	55
22		220	5x11	65	5x11	70	5x11	80
33		330	5x11	80	5x11	90	5x11	95
47		470	5x11	95	5x11	110	6.3x11	130
100		101	6.3x11	160	6.3x11	170	8x11.5	220
220		221	8x11.5	270	8x11.5	300	10x12.5	350
330		331	8x11.5	330	10x12.5	390	10x16	480
470		471	10x12.5	420	10x16	520	10x20	630
1000		102	10x20	740	12.5x20	890	12.5x25	1070
2200		222	12.5x25	1220	16x25	1350	16x35.5	1700
3300		332	16x25	1420	16x35.5	1810	18x35.5	2060
4700		472	16x31.5	1740	18x35.5	2110		
6800		682	18x35.5	2170				
10000		103	20x40	2610				
15000		153	22x50	3270				
22000		223	25x50	3690				



7170 N. Ridgeway
Lincolnwood, IL 60712
Ph: 847-675-1865
Fax: 847-675-3345
Email: sales@icd-sales.com
Website: www.icd-sales.com