

GP Batteries

Product Specification

Model No.: GPPB80



Unit : mm

Product Name	:	GP PowerBank V800C
Description	:	15/30 Mins Battery Charger with AC Adaptor
Special Feature	:	Digital Clock & Easy Check 3-Color LED Icons.
Input Voltage	:	AC100-240V 50/60Hz
Output Voltage	:	DC12V \approx 3.3A
Application	:	For charging 1 to 4 pcs of NiMH AA & AAA batteries
Charging Current	:	AA (1-2 cell) - 7000mA, AA (3-4 cell) - 4000mA, AAA - 3400mA (+/-10%) (When temperature ranges from 10°C to 35°C) AA - 3400mA, AAA - 1700mA (+/-10%) (When temperature ranges from 5°C to 10°C)
Trickle Charge Current	:	AA - 160mA, AAA - 60mA
Charging Time	:	

Type	Size	Battery	Charging Time (mins)	
			1-2 pcs	3-4 pcs
GP NiMH	AA	2700 series	~ 25	~ 43
		2500 series	~ 22	~ 40
		2300 series	~ 20	~ 35
		2100 series	~ 18	~ 33
	AAA	1800 mAh	~ 15	~ 30
		1000 series	~ 19	
		950 series	~ 18	
		850 mAh	~ 17	
		750 mAh	~ 15	

Termination Methods	:	- Δ V: 0-5mV, Temperature Cutoff: 55°C (+5/-8°C) Safety Timer: 40 mins. (1-2 AA/1-4 AAA), 65 mins (3-4 AA)
Ventilation Fan	:	Fan will operate while charging.
MTBF	:	30000 hours (at Ambient Temperature 25°C)
Operating Temperature	:	5°C to 45°C
Storage Temperature	:	-25°C to 60°C



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

06060106180