

**Volt-Check 3.1**

**2-pole voltage tester**



- LED indicator for voltage and phase
- PTC controlled
- polarity detection

**Car-Check**

**2-pole voltage tester for cars**



- Test probe
- Pin with sliding mechanism
- cable 130 cm long
- polarity detection

**Technical specification**

Rated voltage, min.	6 V AC/DC
Rated voltage, max.	400 V AC/DC
Input resistance	4...50 kΩ
Peak resistance voltage	5 kV
Frequency range, min.	0 Hz
Frequency range, max.	100 Hz
Function indicator	LED
DC voltage	6, 50, 120, 400 V
AC voltage	6, 50, 120, 400 V
Operating temperature, min.	-10 °C
Operating temperature, max.	50 °C
Ingress protection class	IP 40
Approval	EN/ IEC 61010
Weight	70 g

**Technical specification**

Rated voltage, min.	3 V DC
Rated voltage, max.	48 V DC
Function indicator	LED
Operating temperature, min.	-10 °C
Operating temperature, max.	50 °C
Weight	57 g

**Ordering data**

Type	Qty.	Order No.
VOLT-CHECK 3.1	1	9918950000
VOLT-CHECK 3.1 2 mm Probes	1	9201560000

**Accessories**

Type	Qty.	Order No.
Protective case	1	9201520000

**Ordering data**

Type	Qty.	Order No.
CAR-CHECK	1	9918970000

**Accessories**

Type	Qty.	Order No.
Protective case	1	9201520000