

No	Part Number	DC Characteristics				AC Characteristics				Switching & Protection				Transient Response				
		V _{cb0} V	I _c A	P _c W	I _{cbo} uA	I _{ceo} uA	V _{ceo} V	V _{cb0} V	V _{cesat} V	V _{besat} V	HFE min	HFE max	t _s (uS) min	t _s (uS) max	t _f uS	V _f V		
1	BLD102D	TO-92	600	1.8	10	100	250	400	9	0.3	0.6	1	10	40	2	4	0.9	2
2	BLD112D	TO-92	600	1	12	100	250	400	9	0.2	0.5	1.2	10	40	1.5	3	1	2
3	BLD122D	TO-92	600	1.2	13	100	250	400	9	0.5	0.6	1.2	10	40	1.5	3.5	0.8	2.6
4	BLD122D	TO-126	600	1.2	25	100	250	400	9	0.5	0.6	1.2	10	40	2	3.5	0.8	2.6
5	BLD132D	TO-92	600	1.5	18	10	30	400	9	0.3	0.9	1.2	10	40	2	4	-	2
6	BLD132D	TO-126	600	1.5	28	10	30	400	9	0.3	0.9	1.2	10	40	2	4	-	2
7	BLD132D	TO-126	600	1.8	30	100	250	400	9	0.3	0.9	1.2	10	40	2	4	-	2
8	BLD132D	TO-220	600	1.5	40	10	30	400	9	0.3	0.9	1.2	10	40	2	4	-	2
9	BLD133D	TO-92	700	2	23	100	250	400	9	0.5	0.6	1.2	10	40	2	3.5	0.8	1.7
10	BLD128DA	TO-220	700	3	65	100	250	400	9	0.5	1	1.3	10	40	2	4	0.8	1.5
11	BLD128D	TO-220	700	5	75	100	250	400	9	0.3	0.8	1.1	10	40	1.5	4	0.8	2
12	BLD137DA	TO-220	700	8	80	100	250	400	9	0.4	1.5	1.2	10	40	4	7	0.8	2
13	BLD137D	TO-220	700	8	90	100	250	400	9	0.5	1.5	1.3	10	40	4	7	0.8	1.6
14	BLD139D	TO-220	700	12	100	100	250	400	9	0.6	0.9	1.2	10	40	5	8	0.8	1.6